

## CÂBLES EN ACIER STANDARDS

6X25+O FILLER

EN 12385-4

DIAM. CABLE	DIAM. ALAM.	SECTION CABLE	POIDS	CRM1770 N/MM <sup>2</sup>	CRM1770 N/MM <sup>2</sup>	CRM1960 N/MM <sup>2</sup>	CRM1960 N/MM <sup>2</sup>
MM.	MM	MM <sup>2</sup>	KGS/MT	180 KP/MM <sup>2</sup> KN	180 KP/MM <sup>2</sup> KP	200 KP/MM <sup>2</sup> KN	200 KP/MM <sup>2</sup> KP
6	0,4	17	0,144	22,7	2.314	25,1	2.559
7	0,45	23	0,196	30,9	3.150	34,2	3.486
8	0,51	30	0,256	40,3	4.108	44,7	4.557
9	0,57	38	0,324	51	5.199	56,5	5.759
10	0,64	48	0,4	63	6.422	69,8	7.115
11	0,7	57	0,484	76,2	7.768	84,4	8.603
12	0,76	68	0,576	90,7	9.246	100	10.194
13	0,84	81	0,676	106	10.805	118	12.029
14	0,9	94	0,784	124	12.640	137	13.965
16	1,02	122	1,02	161	16.412	179	18.247
18	1,14	153	1,3	204	20.795	226	23.038
20	1,28	191	1,6	252	25.688	279	28.440
22	1,4	229	1,94	305	31.091	338	34.455
24	1,53	273	2,3	363	37.003	402	40.979
26	1,65	320	2,7	426	43.425	472	48.114
28	1,8	374	3,14	494	50.357	547	55.759
32	2,04	487	4,1	645	65.749	715	72.885
36	2,16	610	5,18	817	83.282	904	92.151
40	2,54	757	6,4	1010	102.956	1120	114.169
44	2,79	912	7,74	1220	124.363	1350	137.615
48	3,05	1089	9,22	1450	147.808	1610	164.118
52	3,3	1278	10,8	1700	173.293	1890	192.661
56	3,56	1482	12,5	1980	201.835	2190	223.242
60	3,81	1700	14,4	2270	231.397	2510	255.861

