


CÂBLES EN ACIER STANDARDS

6X36+1 WS

EN 12385-4



DIAM. CABLE	DIAM. ALAM.	SECTION CABLE	POIDS	CRM 1770 N/MM ²	CRM 1770 N/MM ²	CRM 1960 N/MM ²	CRM 1960 N/MM ²
MM.	MM	MM ²	KGS/MT	180 KP/MM ² KN	180 KP/MM ² KP	200 KP/MM ² KN	200 KP/MM ² KP
8	0,44	25	0,235	37,4	3.812	41,4	4.220
9	0,51	33	0,297	47,3	4.822	52,4	5.341
10	0,55	40	0,367	58,4	5.953	64,7	6.595
11	0,62	50	0,444	70,7	7.207	78,3	7.982
12	0,66	58	0,528	84,1	8.573	93,1	9.490
13	0,74	70	0,62	98,7	10.061	109	11.111
14	0,8	81	0,719	114	11.621	127	12.946
16	0,89	105	0,94	150	15.291	166	16.922
18	1,01	134	1,19	189	19.266	210	21.407
20	1,1	165	1,47	234	23.853	259	26.402
22	1,23	198	1,78	283	28.848	313	31.906
24	1,33	235	2,11	336	34.251	373	38.022
26	1,45	276	2,48	395	40.265	437	44.546
28	1,6	325	2,88	458	46.687	507	51.682
30	1,67	364	3,3	525	53.517	582	59.327
31	1,75	390	3,53	561	57.187	622	63.405
32	1,8	420	3,76	598	60.958	662	67.482
33	1,85	448	4,00	636	64.828	704	71.766
34	1,91	476	4,26	675	68.807	747	76.181
35	1,95	502	4,50	716	72.939	792	80.728
36	2	528	4,76	757	77.166	838	85.407
38	2,12	587	5,3	843	85.933	934	95.160
40	2,23	650	5,87	935	95.311	1040	106.014
42	2,36	720	6,48	1030	104.955	1147	116.881
44	2,45	787	7,11	1130	115.189	1250	127.421
45	2,5	823	7,44	1187	120.950	1316	134.174
46	2,57	858	7,76	1236	125.968	1366	139.268
48	2,7	934	8,46	1350	137.615	1490	151.886
50	2,79	1012	9,17	1460	148.828	1617	164.807
52	2,9	1099	9,92	1580	161.060	1750	178.389
54	3,01	1182	10,69	1702	173.458	1887	192.376
55	3,1	1226	11,09	1765	179.876	1958	199.567
56	3,15	1272	11,5	1830	186.544	2030	206.932
60	3,36	1461	13,2	2100	214.067	2330	237.513

