

DIAM. CABLE	DIAM. ALAM.	SECTION CABLE	POIDS	CRM 1770	CRM 1770	CRM 1960	CRM 1960
				N/MM ²	N/MM ²	N/MM ²	N/MM ²
MM.	MM	MM ²	KGS/MT	180 KP/MM ² KN	180 KP/MM ² KP	200 KP/MM ² KN	200 KP/MM ² KP
2	0,15	1,7	0,0152	2,56	261	2,84	290
2,5	0,18	3	0,0238	4,01	408	4,44	452
3	0,2	8	0,0343	5,77	588	6,39	651
4	0,26	11	0,061	10,3	1050	11,4	1162
5	0,33	13	0,0953	16	1631	17,7	1804
6	0,39	16	0,137	23,1	2.355	25,5	2.599
7	0,45	21	0,187	31,4	3.201	34,8	3.547
8	0,51	28	0,243	41	4.179	45,4	4.628
9	0,58	36	0,308	51,9	5.291	57,5	5.861
10	0,64	44	0,381	64	6.524	70,9	7.227
11	0,7	53	0,461	77,5	7.900	85,8	8.746
12	0,77	64	0,548	92,3	9.409	102	10.398
13	0,83	74	0,643	108	11.009	120	12.232
14	0,89	86	0,746	126	12.844	139	14.169
16	1,01	111	0,974	164	16.718	182	18.552
18	1,15	143	1,23	208	21.203	230	23.445
20	1,27	176	1,52	256	26.096	284	28.950
22	1,39	211	1,84	310	31.600	343	34.964
24	1,51	249	2,19	369	37.615	409	41.692
26	1,68	301	2,57	433	44.139	480	48.930
28	1,8	346	2,98	502	51.172	556	56.677
32	2,07	458	3,9	656	66.871	727	74.108
36	2,31	572	4,93	830	84.608	920	93.782
40	2,57	708	6,09	1025	104.485	1135	115.698
44	2,82	852	7,37	1.240	126.402	1374	140.061
48	3,08	1017	8,77	1.476	150.459	1635	166.667
52	3,3	1193	10,3	1.733	176.656	1919	195.617
56	3,6	1384	12	2.009	204.791	2225	226.809

