

CÂBLES EN ACIER STANDARDS

7X7+0

EN 12385-4

| DIAM. CABLE | DIAM. ALAM. | SECTION CABLE | POIDS | CRM 1770 N/MM ² | CRM 1770 N/MM ² | CRM 1960 N/MM ² | CRM 1960 N/MM ² |
|-------------|-------------|-----------------|--------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| MM. | MM | MM ² | KGS/MT | 180 KP/MM ² KN | 180 KP/MM ² KP | 200 KP/MM ² KN | 200 KP/MM ² KP |
| 1 | 0,11 | 0,5 | 0,0039 | 0,64 | 65 | 0,70 | 72 |
| 1,5 | 0,16 | 1 | 0,0087 | 1,43 | 146 | 1,58 | 161 |
| 2 | 0,21 | 2 | 0,0154 | 2,54 | 259 | 2,81 | 286 |
| 2,5 | 0,28 | 3 | 0,0240 | 3,98 | 405 | 4,40 | 449 |
| 3 | 0,32 | 4 | 0,0346 | 5,72 | 583 | 6,33 | 645 |
| 4 | 0,42 | 8 | 0,0614 | 10,2 | 1040 | 11,3 | 1152 |
| 5 | 0,53 | 12 | 0,096 | 15,9 | 1621 | 17,6 | 1794 |
| 6 | 0,63 | 17 | 0,138 | 22,9 | 2.334 | 25,3 | 2.579 |
| 7 | 0,74 | 12 | 0,188 | 31,1 | 3.170 | 34,5 | 3.517 |
| 8 | 0,9 | 30 | 0,246 | 40,7 | 4.149 | 45,0 | 4.587 |
| 9 | 1 | 38 | 0,311 | 51,5 | 5.249 | 57,0 | 5.810 |
| 10 | 1,1 | 46 | 0,384 | 63,5 | 6.473 | 70,4 | 7.176 |
| 11 | 1,2 | 57 | 0,465 | 76,9 | 7.838 | 85,1 | 8.674 |
| 12 | 1,3 | 67 | 0,553 | 91,5 | 9.327 | 101 | 10.295 |
| 13 | 1,45 | 78 | 0,649 | 107 | 10.907 | 119 | 12.130 |
| 14 | 1,5 | 90 | 0,753 | 125 | 12.741 | 138 | 14.066 |
| 16 | 1,75 | 120 | 0,983 | 163 | 16.615 | 180 | 18.347 |
| 18 | 1,95 | 151 | 1,24 | 206 | 20.998 | 228 | 23.240 |
| 20 | 2,2 | 184 | 1,54 | 254 | 25.890 | 281 | 28.642 |
| 22 | 2,4 | 223 | 1,86 | 308 | 31.395 | 341 | 34.758 |
| 24 | 2,6 | 265 | 2,21 | 366 | 37.307 | 405 | 41.282 |
| 26 | 2,75 | 311 | 2,6 | 430 | 43.830 | 476 | 48.519 |
| 28 | 3 | 360 | 3,01 | 498 | 50.761 | 552 | 56.266 |
| 32 | 3,4 | 470 | 3,93 | 651 | 66.357 | 721 | 73.492 |
| 36 | 3,8 | 595 | 4,98 | 824 | 83.991 | 912 | 92.960 |
| 40 | 4,25 | 735 | 6,14 | 1020 | 103.969 | 1130 | 115.181 |

